# **KEL-QUICK | Split multi cable transit frames**

for cables with connectors, tool-free assembly / IP54





RoHS













The KEL-QUICK range is a compact system to route and seal pre-terminated cables as well as conduits or pneumatic hoses utilising split QT and QTMB grommets. After populating the entry frame with QT / QTMB grommets and cables, the cover lid is snapped onto the frame without using tools. Routing and sealing with IP54 for cable diameters from 1 to 29 mm.

The KEL-QUICK frames match exactly the cut-out dimensions for 10-, 16- and 24-pin standard industrial connectors. The KEL-QUICK-B frames match the cut-out dimensions  $46\times36$  mm. These KEL-QUICK frames can either be screw mounted or simply snapped into the <u>KEL-SNAP frame</u>.

The single-row KEL-QUICK-E versions are particularly suited for flat connectors. The small frames are ideal for applications with limited space.

A flat rubber gasket is included in the shipment.

It is also possible to integrate threaded bushings. Please ask us about your desired variant.

The version with threaded bushings enables the cable entry frame to be screwed onto the housing from the inside out. This protects against vandalism and tampering with the housing from the outside.

### **Specifications**

IP rating (EN 60529)	IP54
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	UV-resistant, silicone free, halogen free, anti-corrosive
Mounting options	Screw type mounting,Snap-in with KEL-SNAP
Mounting height	17 mm

### **Advantages & benefits**

- Fast and easy snap-in assembly of the frame
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- High cable density, wide variety of grommets
- Greatly increased cable density when using double or quadruple grommets

## **Product types & sizes**

KEL-QUICK 24|10

EAN
Package quantity
For max. no. of cables
Max. cable diameter
Length
Width

Part No.

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material

Screw material

17 mm 17 mm 112 × 36 mm

5.8 mm

Mild steel, galvanically zinc plated

Suitable for grommets

10 x QT small

KEL-QUICK 24|7

 Part No.
 42412

 EAN
 4251269321559

 Package quantity
 10

 For max. no. of cables
 25

 Max. cable diameter
 29 mm

 Length
 147 mm

 Width
 58 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Screw material

17 mm 17 mm 112 × 36 mm 4 5,8 mm

Mild steel, galvanically zinc

#### KEL-OUICK 24/4 Part No. 42413 Height 17 mm 4251269321566 EAN Mounting height 17 mm 112 × 36 mm Package quantity 10 Cut-out size For max. no. of cables 10 No. of screw holes Max. cable diameter 29 mm Diam. of screw holes 5,8 mm 147 mm Mild steel, galvanically zinc Length Screw material Width 58 mm plated Suitable for grommets 2 x QT small 2 x QT large KEL-QUICK 16|8 42418 17 mm Part No. Height EAN 4251269308703 Mounting height 17 mm Package quantity 10 Cut-out size 86 × 36 mm For max. no. of cables 32 No. of screw holes Max. cable diameter 15 mm Diam. of screw holes 5,8 mm 120 mm Length Mild steel, galvanically zinc Screw material Width 58 mm plated Suitable for grommets 8 x QT small KEL-QUICK 16|5 Part No. 42425 Height 17 mm 4251269321573 EAN Mounting height 17 mm 86 × 36 mm Package quantity 10 Cut-out size 20 For max. no. of cables No. of screw holes Max. cable diameter 29 mm Diam. of screw holes 5.8 mm Length 120 mm Screw material Mild steel, galvanically zinc Width 58 mm plated Suitable for grommets 4 x QT small 4 x QT large KEL-QUICK 16|2 Part No. 42426 Height 17 mm 4251269321580 17 mm EAN Mounting height Package quantity 10 Cut-out size 86 × 36 mm For max. no. of cables 2 No. of screw holes 4 Max. cable diameter 29 mm Diam. of screw holes 5,8 mm Mild steel, galvanically zinc Length 120 mm Screw material Width 58 mm plated Suitable for grommets 2 x QT large KEL-QUICK 10|6 Part No. 42420 Height 17 mm EAN 4251269316821 Mounting height 17 mm Package quantity 10 65 x 36 mm Cut-out size No. of screw holes For max, no, of cables 24 Max. cable diameter 15 mm Diam. of screw holes 5,8 mm Lenath 98 mm Screw material Mild steel, galvanically zinc Width 58 mm plated 6 x QT small Suitable for grommets KEL-QUICK 10|3 42427 17 mm Part No. Height FAN 4251269321597 Mounting height 17 mm 0 Package quantity 10 Cut-out size 65 × 36 mm For max. no. of cables No. of screw holes

Max. cable diameter

Length

Width

29 mm

98 mm

58 mm

Diam. of screw holes

Suitable for grommets

Screw material

5,8 mm

plated 2 x QT small

1 x QT large

Mild steel, galvanically zinc

#### **KEL-QUICK-B4** 42434 Part No. Height 17 mm 4251269308727 17 mm EAN Mounting height 0 Package quantity 10 Cut-out size 46 × 46 mm For max. no. of cables 16 No. of screw holes 4 Max. cable diameter 15 mm Diam. of screw holes 5,8 mm 0 73 mm Mild steel, galvanically zinc Length Screw material Width 58 mm plated Suitable for grommets 4 x QT small **KEL-QUICK-B1** Part No. 42435 Height 17 mm EAN 4251269333231 Mounting height 17 mm 0 0 Package quantity Cut-out size 46 × 46 mm For max. no. of cables No. of screw holes Max. cable diameter 29 mm Diam. of screw holes 5,8 mm 0 0 Length 73 mm Screw material Mild steel, galvanically zinc Width 58 mm plated Suitable for grommets 1 x QT large **KEL-QUICK-E5** Part No. 42424 Height 17 mm EAN 4251269316869 Mounting height 17 mm Package quantity 10 Cut-out size 112 × 24 mm For max. no. of cables 20 No. of screw holes 2 Max. cable diameter 15 mm Diam. of screw holes 5,8 mm Length 147 mm Screw material Mild steel, galvanically zinc Width 38 mm plated Suitable for grommets 5 x QT small **KEL-QUICK-E4** Part No. 42423 Height 17 mm EAN 4251269316852 Mounting height 17 mm Package quantity 10 Cut-out size 86 × 24 mm For max. no. of cables 16 No. of screw holes Max. cable diameter 15 mm Diam. of screw holes 5,8 mm Length 120 mm Screw material Mild steel, galvanically zinc Width 38 mm plated Suitable for grommets 4 x QT small **KEL-QUICK-E3** Part No. 42422 Height 17 mm 4251269316845 Mounting height 17 mm Package quantity 10 Cut-out size 65 × 24 mm For may no of cables No of screw holes

FOI IIIax. IIO. OI Cables	12	No. of sciew fibles	4
Max. cable diameter	15 mm	Diam. of screw holes	5,8 mm
Length	98 mm	Screw material	Mild steel, galvanically zinc
Width	38 mm		plated
		Suitable for grommets	3 x QT small

KEL-QUICK-E2 Part No. 42421 Height 17 mm	
EAN 4251269316838 Mounting height 17 mm	
Package quantity 10 Cut-out size 43 × 24 mm	
O For max. no. of cables 8 No. of screw holes 2	
Max. cable diameter 15 mm Diam. of screw holes 5,8 mm	
Length 73 mm Screw material Mild steel, galv	anically zinc

38 mm

Width



plated

2 x QT small

Suitable for grommets

