KEL-FA | Split multi cable entry frames

for cables with connectors, tool-free assembly / IP54 / UL Type 12



The KEL-FA range is a compact system to route and seal pre-terminated cables as well as conduits or pneumatic hoses utilising KT series grommets. After populating the entry frame with grommets and cables, the cover is put on and the two clamping levers are locked with the lower part by pressing them down. The twist-proof construction of the KEL-FA enables intuitive assembly. Routing and sealing with IP54 / UL Type 12 for cable diameters from 1 to 35 mm.

The KEL-FA frames match exactly the cut-out dimensions for 10-, 16- and 24-pin standard industrial connectors. These KEL-FA frames can either be screw mounted or simply snapped into the <u>KEL-SNAP frame</u>.

IP54











Specifications

IP rating (EN 60529)	IP54
UL Type (UL 50E)	UL Type 12
Material	Polyamide
Flame class	UL94-V0, self-extinguishing
Operating temperature	-40 C° to 140 C°
Properties	UV-resistant, silicone free, anti- corrosive, halogen free
Mounting options	Screw type mounting,Snap-in with KEL-SNAP

Advantages & benefits

- Integrated sealing
- Quick assembly without tools
- Strain relief according to EN 62444 (when using KT single hole grommets)
- Very high cable density with multi-hole grommets
- High flexibility with multi-range grommets and the IMAS-CONNECT™ system
- Warranty on pre-terminated cables remains
- Retrofits, repairs and maintenance can be done much more easily and quickly
- Wide variety

Product types & sizes

KEL-FA 24 10					
6					For

rait No.
EAN
Package quantity
For max. no. of cable
Max. cable diameter
Length
Width

Part No

	55241
	4251269324796
	10
les	40
er	15 mm
	147 mm
	62 mm

Height
Mounting height
Cut-out size
No. of screw holes
Diam. of screw holes
Suitable for grommets

22 mm
22 mm
112 × 36 mm
4
6 mm
10 x KT small

		•	
40	_		H01
11-1			11-11
10			
l I			

KEL-FA 24|7

Part No.	55247
EAN	4251269324802
Package quantity	10
For max. no. of cables	25
Max. cable diameter	35 mm
Length	147 mm
Width	62 mm

Height	22 mm
Mounting height	22 mm
Cut-out size	112 × 36 mm
No. of screw holes	4
Diam. of screw holes	6 mm
Suitable for grommets	6 x KT small
	1 x KT large

KEL-FA 24|4



Part No. EAN Package quantity For max. no. of cables Max. cable diameter

Length Width

55244 4251269324819 10

35 mm 147 mm 62 mm

Height


Mounting height Cut-out size No. of screw holes

Diam. of screw holes Suitable for grommets 22 mm 22 mm

112 × 36 mm

6 mm 2 x KT small 2 x KT large

KEL-FA 16|8



Part No. EAN Package quantity

For max. no. of cables Max. cable diameter Length Width

55168


4251269324826

Height

Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets 22 mm 22 mm 86 × 36 mm

6 mm 8 x KT small

KEL-FA 16|5



Part No. EAN

Package quantity For max. no. of cables Max. cable diameter

Lenath Width

55165

4251269324833

Height

Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets 22 mm 22 mm 86 × 36 mm

6 mm 4 x KT small

1 x KT large

KEL-FA 16|2



Part No. EAN

Package quantity For max. no. of cables Max. cable diameter

Length Width

4251269324840 10 2

35 mm 120 mm 62 mm

55162


Height

Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets 22 mm 22 mm 86 × 36 mm

4

6 mm 2 x KT large

KEL-FA 10|6



Part No. FAN

Package quantity For max. no. of cables Max. cable diameter

Length Width

55216

4251269324857 10

24 15 mm 100 mm 62 mm


Height

Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets 22 mm 22 mm

65 × 36 mm

6 mm 6 x KT small

KEL-FA 10|3



Part No.

Width

Package quantity For max. no. of cables Max. cable diameter Length

55212

4251269324864 10 35 mm 100 mm 62 mm

Height

Mounting height Cut-out size No. of screw holes Diam. of screw holes Suitable for grommets 22 mm 22 mm

65 × 36 mm

6 mm

2 x KT small 1 x KT large



smart cable management